


YOGA ERGO FUSION



YOGA ERGO FIRE and YOGA ERGO STAT rolled into one: YOGA ERGO FUSION is characterized by low flammability and an excellent conductivity.



Sizes:

65 cm × 95 cm, 65 cm × 185 cm
95 cm × 125 cm, 95 cm × 185 cm
Special sizes on request

Thickness: 14 mm

Weight: 5 kg/m²

Hardness: 30° ±5 Shore A

Surface:

nubs, closed

Material:

polyurethane (PU)

Fire behavior:

B1 (DIN 4102)

Slip resistance:

good / R10 (DIN 51130)

Displacement space:

V10 (DIN 51130)

Conductivity:

DIN IEC 61340-4-1/

ESD1 × 10⁸ Ohm

Accessories:

grounding module and
grounding cable

Characteristics


- silicone-free and fireproof workplace mat with very good conductivity, ideal to use at ESD workstations or production facilities with sensitive devices
- available in special shapes and sizes
- noise-insulating and slip resistant surface
- beveled edges on all sides reduce trip hazards
- conditionally resistant to oils and chemicals (please request a test sample)
- provides excellent insulations against cold floors
- temperature-resistant (-40 °C to +80 °C)
- can be driven on (with hand truck, hand cart or material shuttles)
- made in Germany

Cleaning Instructions

High pressure cleaner or industrial dry vacuum cleaner are ideal for an accurate cleaning. For a simple and quick cleaning you can also wash it down with water or simply sweep it off.

Installation

Fixing or gluing is not necessary.



black