



YOGA SOLID OIL



For large and individually manufactured dry working areas. Flexible in use, for instance in industry and trade, especially where chemicals and oils are used.



Sizes:

90 cm × 90 cm

Thickness: 17 mm

Weight: 15,7 kg/m²

Surface:

closed surface with structure

Material:

100 % nitrile rubber (NBR)

Slip resistance:

good / R10 (DIN EN 16165)

Accessories:

edging with corner

97 cm × 7 cm

Characteristics


- YOGA SOLID OIL is resistant to oils and chemicals (please request a test sample)
- flexible modular system: the individual mats can be plugged together to form a floor covering that covers the entire area
- the specially designed bottom side of YOGA SOLID OIL in combination with the grained surface create a cushioning effect so that fragile material is protected when dropped
- can be linked to YOGA OCTA mats (for different application areas)
- thanks to the bevelled edging YOGA SOLID OIL is passable with hand trucks, hand carts, etc. and reduce the risk of tripping

Cleaning Instructions

High pressure cleaner or industrial dry vacuum cleaner are ideal for an accurate cleaning. For a simple and quick cleaning you can also wash it down with water or simply sweep it off.

Installation


One mat is equipped with nubs on two sides and eyelets on the other two sides. This allows them to be quickly and easily plugged into each other.



black



yellow edge



black edge