

YOGA ERGO STAT



Mat with very good conductivity for ESD workplaces or production facilities with sensitive devices.



Sizes:

65 cm × 95 cm, 65 cm × 185 cm
95 cm × 125 cm, 95 cm × 185 cm
Special sizes on request

Thickness: 14 mm

Weight: 5 kg/m²

Hardness: 30° ±5 Shore A

Surface:

nubs, closed

Material:

polyurethane (PU)

Fire behavior:

B2 (DIN 4102)

Slip resistance:

good / R10 (DIN 51130)

Displacement space:

V10 (DIN 51130)

Conductivity:

DIN IEC 61340-4-1 /
ESD 1 × 10⁵–10⁷ Ohm

Accessories:

grounding module and
grounding cable

Characteristics

- silicone-free mat with very good conductivity, also available in special shapes and sizes
- noise-insulating and slip resistant surface
- made in Germany
- beveled edges on all sides reduce trip hazards
- conditionally resistant to oils and chemicals (please request a test sample)
- provides excellent insulations against cold floors
- temperature-resistant (–40 °C to +80 °C)
- can be driven on (with hand truck, hand cart or material trolleys)

Cleaning Instructions

High pressure cleaner or industrial dry vacuum cleaner are ideal for an accurate cleaning. For a simple and quick cleaning you can also wash it down with water or simply sweep it off.

Installation

Fixing or gluing is not necessary.



black